

TEUPEN[®]
...access redefined

LE015GTplus

Working height:
15.40 m

Lateral reach:
7.90 m

Machine width:
0.78 m

Machine height:
1.99 m

Weight:
2,200 kg

- Compact design, travels through a single door
- Light, low surface load for use on sensitive flooring
- Smooth, proportional electro-hydraulic controls
- Reliable and comprehensive safety control system
- Full height and outreach with 200 kg basket load
- Automatic, self leveling outriggers
- Setup on slopes up to 21 %
- Dual power (Petrol and electric) for indoor and outdoor use

[www.**TEUPEN**.com](http://www.teupen.com)

Teupen Maschinenbau GmbH
phone +49 2562 8161 0
fax +49 2562 8161 888
mail@teupen.com



Compact tracked boom lift - LE015GTplus

Accessing jobsites at height safely and efficiently often poses unsolvable challenges to building managers. Narrow entrances, confined work areas and floor load restrictions can make the use of standard aerial lifts impossible.

With the LEO Series[®], Teupen offers the original tracked aerial lift in a complete range for demanding indoor and rugged outdoor applications from 13 to outstanding 50 metres working height.



LEOSERIES




LEO15GTplus



The cable remote control gives the operator a better overview when driving and setting up the lift.



For passing narrow entrances the basket is detachable. The LEO15GTplus passes all standard single doors.



The freely movable jib arm increases the versatility of the lift when operation around obstacles and accessing hard to reach spots.



Every Teupen lift up to 18 metres working height has forklift pockets for easier handling and loading.

Top features:

- Compact** – Fits through standard single door
- Light** – Low ground pressure to protect sensitive surfaces
- Versatile** – Highest maneuverability on white rubber tracks
- Easy** – Automatic self-levelling stabilisers
- Power** – Multiple power sources for indoor and outdoor work

Overview: LEO Series models from 13 to 18 metres working height

Model	LEO13GT	LEO15GT	LEO15GTplus	LEO18GT	LEO18GTplus
Working height	12,75 m	14,70 m	15,40 m	17,60 m	18,30 m
Outreach	6,05 m	7,60 m	7,90 m	7,40 m	8,50 m
Weight	1400 kg	1780 kg	2200 kg	2400 kg	2450 kg
Width	0,78 m	0,78 m	0,78 m	0,78 m	0,78 m
Movable Jib	-	-	✓	-	✓
Adjustable tracks	-	Option	✓	✓	✓
Diesel engine	Hatz (O)	Hatz (O)	Kubota (O)	Kubota (O)	Kubota (O)
Gas/petrol engine	Subaru (O)	Subaru (S)	Vanguard (S)	Vanguard (S)	Vanguard (S)

LEO = Model, Number = Metric Working height, G = Articulated, T = Telescopic, S = Standard, O = Optional